

INTEGRATED DC RTS RECEIVER

Ref 1870142

Basic information

- 24V DC RTS receiver.
 - Dedicated to be integrated in a headrail.
 - Suitable for most types of rail, from 25x25mm.
 - Compatible with LV25/LW25.
 - Compatible with all RTS control, including Modulis remote control, Sunis sun sensor and Impressario control.
-
- RTS receiver for 25x25 headrail integration.
 - For lift only and lift / tilt applications- compatible with Modulis remote control.
 - Intermediate position / slat orientation.
 - Use only regulated power supplies with this product
 - Dimensions: 97 mm wide, 24 x 24 mm diameter.
 - Contact capacity: 1.3 A



Main technical information

Application(s)	Motorised blinds
Radio Frequency	433,42 MHz
Nominal Voltage / Frequency	24V DC
Color / Finish	Black
Length (L3)	150 mm
Width	25 mm
Height	25 mm
Protection Index	IP 20

Technical information

Technology

Radio Frequency	433,42 MHz
-----------------	------------

Standard

Insulation class	III
Protection Index	IP 20

Electrical

Output type of contact	24 VDC
Nominal Voltage / Frequency	24V DC

Dimension

Weight	0,030 Kg
Length (L3)	150 mm
Width	25 mm
Height	25 mm

Other

Color / Finish	Black
----------------	-------